



nov-17

## DATASHEET LARO PVC 83

### General definition :

Packaging tape with a PVC (Polyvinylchloride) foil and provided with a glue layer based on natural rubber.

### Features:

- Prettiest printing results
- Quiet on unrolling
- Fit for various surfaces such as cardboard, paper, plastic, etc.
- Can be torn by hand
- Fit for recycling

### Specifications:

Product type	Glue Layer	Tape thickness In Mμ	Adhesive power on steel	Available Colors
Laro PVC 83	Natural rubber	83±10% tolerance	2,0 N/cm±0,8	

### Storage advice:

#### Temperature:

This product can best be stored at a room temperature in a non humid room. We recommend a constant temperature between 15 and 23 degrees Celsius. If the temperature is lower, it can happen that the tape tears. This can also occur as a result of a damaged tape dispenser. Also using good tools is important. (high quality dispenser) Printed tape is best processed at room temperature.

#### Sunlight /UV

This product can best be stored in a dark room. If too much sunlight (UV radiation) is exposed to the tape, the colour fastness can be affected. There may be deviations in the colour fastness.

#### Damages

Make sure that the tape rolls do not fall. This prevents damage in the tape that could cause the tape will tear.

#### Shelf life

How long can I keep this product? This depends on the degree to which the above-mentioned storage advice has been complied with. The guideline for a PVC tape is 2.5 - 3 years. No rights can be derived from this guideline.

#### **Visiting address**

Vermeerstraat 15  
7731 SM Ommen  
The Netherlands

#### **Postal address**

Postbus 59  
7730 AB Ommen  
The Netherlands

**E** [info@larotape.nl](mailto:info@larotape.nl)

**W** [www.larotape.nl](http://www.larotape.nl)

**T** +31(0)529 - 45 38 55

**F** +31(0)529 - 45 62 89