



nov-17

DATASHEET LARO PVC 57 coloured

General definition :

Packaging tape with a PVC (Polyvinylchloride) foil and provided with a glue layer based on natural rubber.

Features:

- Prettiest printing results
- Quiet on unrolling
- Fit for various surfaces such as cardboard, paper, plastic, etc.
- Can be torn by hand
- Fit for recycling

Specifications:

Product type	Glue Layer	Tape thickness In Mμ	Adhesive power on steel	Available Colors
Laro PVC 55	Natural rubber	57±10% tolerance	2,0 N/cm±0,6	

Storage advice:

Temperature:

This product can best be stored at a room temperature in a non humid room. We recommend a constant temperature between 15 and 23 degrees Celsius. If the temperature is lower, it can happen that the tape tears. This can also occur as a result of a damaged tape dispenser. Also using good tools is important. (high quality dispenser) Printed tape is best processed at room temperature.

Sunlight /UV

This product can best be stored in a dark room. If too much sunlight (UV radiation) is exposed to the tape, the colour fastness can be affected. There may be deviations in the colour fastness.

Damages

Make sure that the tape rolls do not fall. This prevents damage in the tape that could cause the tape will tear.

Shelf life

How long can I keep this product? This depends on the degree to which the above-mentioned storage advice has been complied with. The guideline for a PVC tape is 2.5 - 3 years. No rights can be derived from this guideline.

Visiting address

Vermeerstraat 15
7731 SM Ommen
The Netherlands

Postal address

Postbus 59
7730 AB Ommen
The Netherlands

E info@larotape.nl

W www.larotape.nl

T +31(0)529 - 45 38 55

F +31(0)529 - 45 62 89